

Cemprover



CEMPROVER is another Lafarge product that is used in construction. It is a liquid with adhesive properties recommended for use as a “plaskey” for plastering onto smooth surfaces. It is also used as a general purpose lime sealer and in conjunction with paints to improve adhesion.

APPLICATION

- Applied by brushing vigorously the diluted Cemprover into the surface with a brush to form a close texture.

USES

Used as a primer on:

- Old surfaces bearing cement paint.
- Bricks with sulphates.
- Smooth nonabsorbent cement surfaces.
- Surfaces previously painted with lime wash constraints.
- Should not be used on surfaces that have been previously treated with oil paints or varnishes or when temperatures are very low (below 5°C).

PACKAGING

- Cemprover is available in 5litre containers.

STORAGE

- Keep containers air tight during handling and storage.
- Store Cemprover in a cool dry place. Keep in closed container when not in use.

HEALTH AND SAFETY

- Irritating to eyes and skin. Keep out of reach of children. In case of contact with eyes or skin, wash immediately with plenty of water. Wear suitable protective clothing, gloves and eye/face protection.

TECHNICAL DETAILS

- Nature: Liquid.
- Colour: Milky white.
- Drying time: 6 to 8 hours depending on climatic conditions.
- Dilution ratio: 1: 1 primer to clean water.
- Coverage: Depends on porosity and texture of surface being worked on but ranges from approximately 3m² per litre for brick work to 10m² per litre for smooth cement surfaces.